

NE-PE25H

25L (40Khz) LOW PRESSURE PLASMA ETCHING SYSTEM




NE-PE25H PROFILE

NE-PE25H is a microprocessor controlled desktop plasma treatment system which is dedicated to cleaning and surface activation of a wide range of materials including polymers, metals, glass and ceramics, delivering optimum adhesion properties of otherwise difficult to bond materials.

It is widely used in scientific research institutions, enterprise R&D units and small batch production proofing, including:

- ❖ Plasma cleaning organics
- ❖ Plasma surface activation to improve adhesion
- ❖ PDMS & microfluidic devices
- ❖ PEEK & other engineering polymers
- ❖ PTFE
- ❖ Metals
- ❖ Ceramics
- ❖ Glass & optical devices



NE-PE25H FEATURES

❖ Compact, tabletop unit

Weight: 100KG

Size: 650mm(W)×649mm(D) ×666mm(H)

❖ Easy to install

Only need to connect the equipment with the vacuum pump, and then connect the power supply to use.

❖ Adjustable power settings

The max power is 1000W which can be adjusted continuously.

❖ Stainless steel cavity

Durable high-quality stainless steel dedicated electrodes with tray.

Size : 3800(L)×390(D)×170(H)mm;25L



Shenzhen Naen Tech Co., Ltd

Website: www.cnplasma.com

TEL: (+86) 0173-0267-6848

Email: naentech.plasma@gmail.com

✧ **Self-developed power supply**

Digital high-frequency plasma generator produces high-density contour particles to ensure outstanding cleaning effect.

✧ **MFC high precision control of gas flow**

Two gas channels are standard, supports various process gases, such as oxygen, argon, hydrogen, nitrogen, etc.

✧ **Pro-environment**

Dry processing, low gas emission, no hazardous emissions, no pollution to the air.

✧ **7" Touch screen**

The whole process can be directly set and processed through the touch screen, which is intuitive and the process can be monitored in real time. It can support multiple program recipe processing at the same time.

✧ **Vacuum pump**

Equipped with a high-speed vacuum pump, the ideal vacuum value can be reached within 30 seconds, saving the entire processing time.

✧ **Fast treatment time**

A cycle only takes two to five minutes, and processing times can be set according to demand, with a maximum processing time of 9,999 seconds.

NE-PE25H SPECIFICATIONS

	STANDARD MODEL	OPTIONAL
Overall dimensions		
Size	650mm(W) × 649mm(D) × 666mm(H)	
Weight	100KG(Including vacuum pump)	
Plasma generator		
Power	1000W(Adjusted)	
Frequency	40Khz	
Vacuum chamber		
Cavity material	316 stainless steel, military grade seal	
Cavity volume	25L	
Cavity size	380(L)×390(D)×170(H)mm	
Effective processing range	332 (W) × 320 (D) × 30 (H) mm	
Layers	2	
Discharge electrode		
Electrode	High conductive aluminum alloy special electrode	
Discharge modes	CCP	
Gas Control		
Gas flow controller	MFC	
Flow value	0-500sccm	



Shenzhen Naen Tech Co., Ltd


Website: www.cnplasma.com

TEL: (+86) 0173-0267-6848

Email: naentech.plasma@gmail.com

Gas channel	2 channels(supports various process gases, such as oxygen, argon, hydrogen, nitrogen, etc.)	
Vacuum measurement		
Vacuometer	Pirani high precision resistance vacuum gauge	
Pumping system		
Pumping speed	16 m ³ /H, oil pump	Dry pump
Limiting vacuum	1PA	
Control system		
Touch screen	7"	
PLC	Panasonic	
Software	Plasma control system with independent patent: 3 - level permissions, auto/manual modes, recipe param setup/storage/call, alarm history query, IO monitoring.	
Real-time monitoring	Power, vacuum degree, air pressure, gas flow rate, working hours, etc.	
Alarm function	Vacuum anti-misoperation, power anti-misoperation, air pressure alarm, phase sequence alarm	
Condition		
Power Supply	220V	
Type of air pipe	Φ 6mm	
Gas purity	99.999%	
Gas pressure	0.3-0.6Mpa	
Exhaust port	KF25	

TYPICAL PROCESS RESULTS



Shenzhen Naen Tech Co., Ltd

Website: www.cnplasma.com

TEL: (+86) 0173-0267-6848

Email: naentech.plasma@gmail.com

ABOUT NAEN TECH

Naen Tech are an international leader in the design, development and manufacture of plasma surface treatment systems & advanced plasma processes.

Our products are installed worldwide and trusted to deliver consistent, reliable results in both leading research institutes and in critical manufacturing steps.

We are experts in plasma technology and surface science. We are trusted partners, valued for our courtesy, professionalism and dedication to delivering the correct solution for our clients.

OUR SERVICES

❖ Contract plasma treatment

We have more than 10,000 customer cases around the world, and we are equipped with technicians who can meet the plasma needs of various industries, and will provide a quick, no-nonsense feasibility solution for the surface treatment needs of different segments!

❖ Surface testing laboratory

With a comprehensive suite of surface analysis equipment, we are able to conduct a wide range of surface property tests, both before and after plasma treatment, in order to provide you a professional report with the whole pictures and videos.

❖ After sales support

The equipment is guaranteed for one year free of charge and provides lifetime technical services. If the equipment fails (non-human damage), we will arrange after-sales personnel to follow up within 24 hours until the fault is eliminated.

❖ Rental plasma systems

We carry a wide range of our standard equipment in stock and available for short or long term hire. This is particularly useful for in-house proof of concept trials or to satisfy short term contract work.

❖ Method development

We have invested significantly in laboratory facilities to assess, test and investigate all aspects of plasma surface modification on a wide range of materials. Coupled with extensive in-house and real-world knowledge, we can usually deliver a tailored treatment quickly and efficiently to suit your individual product or production needs.



Shenzhen Naen Tech Co., Ltd

Website: www.cnplasma.com

TEL: (+86) 0173-0267-6848

Email: naentech.plasma@gmail.com